



Product Service

CERTIFICATE

No. Z1 043527 0006 Rev. 01

Holder of Certificate: **Roth GmbH**
Kohlbergstr. 5
72213 Altensteig-Spielberg
GERMANY

Certification Mark:



Product: **Sanitary aids**

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition, the certification holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier.

All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 713142443

Valid until: 2029-04-15

Date, 2024-04-19

(Torsten Zimmer)

CERTIFICATE

No. Z1 043527 0006 Rev. 01

Model(s):

1400220 S, 1400221 S, 1400222 S, 1400223 S, 1400224 S, 1400225 S, 1400226 S, 1400226 SCL, 1400227 S, 1400227 SCL, 1400228 S (Kids), 1400229 S (Kids), 1400222H2 S, 1400223H3 S, 1400226H6 S, 1400227H7 S, 1400241 S, 1400242 S, 1400243 S, 1400244 S, 1400261 S, 1400262 S, 1400263 S, 1400264 S, 1400265 S, 1400266 S, 1400268 S (Kids), 1400269 S (Kids)

Parameters:

Type:	Handle length:	Ø-handle:	Material:	max. user weight:
Mobile grab rail with vacuum safety indicator				
1400220 S	110 mm	35 mm	PVC/PA 6.6	105 kg
1400221 S	220-345 mm	35/24 mm	PVC/PA 6.6	85 kg
1400222 S	340-465 mm	35/24 mm	PVC/PA 6.6	85 kg
1400223 S	440-565 mm	35/24 mm	PVC/PA 6.6	85 kg
1400224 S	665-790 mm	35/24 mm	PVC/PA 6.6	80 kg
1400225 S	210 mm	35 mm	PVC/PA 6.6	100 kg
1400226 S	350 mm	35 mm	PVC/PA 6.6	95 kg
1400226 SCL (ChromLook)	350 mm	35 mm	PVC/PA 6.6	95 kg
1400227 S	650 mm	35 mm	PVC/PA 6.6	95 kg
1400227 SCL (ChromLook)	650 mm	35 mm	PVC/PA 6.6	95 kg
1400228 S (Kids)	170 mm	26 mm	PVC/PA 6.6	75 kg
1400229 S (Kids)	310 mm	26 mm	PVC/PA 6.6	75 kg
Mobile angle-adjustable telescopic handle with vacuum safety indicator				
1400222H2 S	340-465 / 340-465 mm	35/24 mm	PVC/PA 6.6/POM	85 kg
1400223H3 S	440-565 / 440-565 mm	35/24 mm	PVC/PA 6.6/POM	85 kg
1400226H6 S	350 / 350 mm	35 mm	PVC/PA 6.6/POM	95 kg
1400227H7 S	650 / 650 mm	35 mm	PVC/PA 6.6/POM	95 kg
QuattroPlus grab rail with vacuum safety indicator				
1400241 S	200 - 325 mm	35/24 mm	PVC/PA 6.6/POM	160 kg
1400242 S	320 - 445 mm	35/24 mm	PVC/PA 6.6/POM	160 kg
1400243 S	420 - 545 mm	35/24 mm	PVC/PA 6.6/POM	160 kg
1400244 S	645 - 770 mm	35/24 mm	PVC/PA 6.6/POM	150 kg
Mobile QuattroPower entry and exit help with vacuum safety indicator				
1400261 S	860 mm	35 mm	PVC/PA 6.6/POM	80 kg
1400262 S	980 mm	35 mm	PVC/PA 6.6/POM	80 kg
1400263 S	740 mm	35 mm	PVC/PA 6.6/POM	80 kg
1400264 S	850 mm	35 mm	PVC/PA 6.6/POM	80 kg
QuattroPower supporting handle with vacuum safety indicator				
1400265 S	390 mm	35 mm	PVC/PA 6.6/POM	80 kg
1400266 S	390 + 120 mm	35/35 mm	PVC/PA 6.6/POM	80 kg
1400268 S (Kids)	390 mm	26 mm	PVC/PA 6.6/POM	60 kg
1400269 S (Kids)	390 + 120 mm	26/35 mm	PVC/PA 6.6/POM	60 kg
Accessories (useable and/or installed in the above mentioned products)				
Cardan joint adapter				
1400559			POM	60 kg
Angle joint adapter				
1400558			POM	75 kg
Diagonal joint adapter				
14400557			Alu/POM	120 kg

□

Tested according to: ISO 17966:2016